



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:A361-XXXXXXYS, A364-XXXXXXYS Series
36W Series AU Power Adapter

Application Scenario

- DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps
- Humidifier, Attendance Machine, Portable DVD, TV Antenna
- Networking Item,Aroma Diffuser, LED Strips, Laptops, Mini Fan

Environmental Data

- Operating Temperature: 0~40°C
- Storage Temperature: -10~70°C
- Humidity: 5%~90% Non-Condensing

Standard & Certificates

- IEC 62368 (60950, 60065): CB,CE,GS,UL,RCM,SAA, KC, PSE, CCC, FCC etc.
- IEC 61558: CB, CE, GS, ETL, RCM, PSE, FCC etc.
- IEC 60335: CE, ETL etc.

Efficiency & Enviroment Standard

- Efficiency Level VI
- DOE, CEC, ERP
- RoHS, REACH, CA Prop 65

Main Features

- Universal Input 100~240VAC 47/63Hz
- OVP, OCP, Short-Circuit Protections
- Compact & Stylish Design, MTBF>30,000 Hours

Electrical Data

- Output Voltage: 5~36VDC
- Output Current: 10mA~5000mA
- Ripple & Noise: <120mVp-p

W & D

- Weight: 165g
- External Dimension: 89 x 47 x 32.5mm
- Color Option: White, Black and Customzied

Packaging

- Packed by separate PE bag
- External Carton Box
- Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A361-0505000S	5V DC	5000mA	<120mVp-p	+/-5%	25 Watt
	A361-1352200S	13.5V DC	2200mA	<120mVp-p	+/-5%	29.7 Watt
	A361-1502000S	15V DC	2000mA	<120mVp-p	+/-5%	30 Watt
	A361-1901500S	19V DC	1500mA	<120mVp-p	+/-5%	28.5 Watt
	A361-2401500S	24V DC	1500mA	<120mVp-p	+/-5%	36 Watt
	A364-1203000S	12V DC	3000mA	<120mVp-p	+/-5%	36 Watt