



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:A653-XXXXXXYS, A654-XXXXXXYS Series
65W Series AU Power Adapter

Application Scenario

- DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps
- Humidifier, Attendance Machine, Portable DVD, TV Antenna
- Networking Items,Aroma Diffuser, LED Strips, Laptop, Mini Fan

Environmental Data

- Operating Temperature: 0~40℃
- Storage Temperature: -10~70℃
- Humidity: 5%~90% Non-Condensing

Standard & Certificates

- IEC 62368 (60950, 60065):CB,CE,GS,UL,RCM, KC, KCC, PSE, CCC, EAC, FCC, BSMI, IRAM, UKCA etc.
- IEC 61558: CB, CE, GS, ETL, RCM, PSE, FCC, IRAM etc.
- IEC 61347: CB, CE, GS, ETL, RCM, PSE, CCC, FCC, KC etc.

Efficiency & Enviroment Standard

- Efficiency Level VI
- DOE, CEC, ERP
- RoHS, REACH, CA Prop 65

Main Features

- Universal Input 100~240VAC 47/63Hz
- OVP, OCP, Short-Circuit Protections
- Compact & Stylish Design, MTBF>30,000 Hours

Electrical Data

- Output Voltage: 8~48VDC
- Output Current: 10mA~5000mA
- Ripple & Noise: <120mVp-p

W & D

- Weight: 235g
- External Dimension: 108.5 x 51 x 33.2mm
- Color Option: White, Black and Customzied

Packaging

- Packed by separate PE bag
- External Carton Box
- Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A654-1404000S	14V DC	4000mA	<120mVp-p	+/-5%	56 Watt
	A653-2402500S	24V DC	2500mA	<120mVp-p	+/-5%	60 Watt
	A653-1504000S	15V DC	4000mA	<120mVp-p	+/-5%	60 Watt
	A653-1903420S	19V DC	3420mA	<120mVp-p	+/-5%	65 Watt
	A653-3601800S	36V DC	1800mA	<120mVp-p	+/-5%	65 Watt
	A653-4801354S	48V DC	1354mA	<120mVp-p	+/-5%	65 Watt