



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:A361-XXXXXX, A364-XXXXXX Series
36W Series Interchangeable Power Adapter

Application Scenario

- DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps
- Humidifier, Attendance Machine, Portable DVD, TV Antenna
- Networking Item,Aroma Diffuser, LED Strips, Laptops, Mini Fan

Environmental Data

- Operating Temperature: 0~40℃
- Storage Temperature: -10~70℃
- Humidity: 5%~90% Non-Condensing

Standard & Certificates

- IEC 62368 (60950, 60065): CB,CE,GS,UL,RCM,SAA, KC, PSE, CCC, FCC etc.
- IEC 61558: CB, CE, GS, ETL, RCM, PSE, FCC etc.
- IEC 60335: CE, ETL etc.

Efficiency & Enviroment Standard

- Efficiency Level VI
- DOE, CEC, ERP
- RoHS, REACH, CA Prop 65

Main Features

- Universal Input 100~240VAC 47/63Hz
- OVP, OCP, Short-Circuit Protections
- Compact & Stylish Design, MTBF>30,000 Hours

Electrical Data

- Output Voltage: 5~36VDC
- Output Current: 10mA~5000mA
- Ripple & Noise: <120mVp-p

W & D

- Weight: 167g (Removable AC Plugs Excluded)
- External Dimension: 89 x 47 x 32.5mm
- Color Option: White, Black and Customzied

Packaging

- Packed by separate PE bag
- External Carton Box
- Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A361-0505000I	5V DC	5000mA	<120mVp-p	+/-5%	25 Watt
	A361-0854000I	8.5V DC	4000mA	<120mVp-p	+/-5%	34 Watt
	A361-0904000I	9V DC	4000mA	<120mVp-p	+/-5%	36 Watt
	A361-1203000I	12V DC	3000mA	<120mVp-p	+/-5%	36 Watt
	A361-2401500I	24V DC	1500mA	<120mVp-p	+/-5%	36 Watt
	A364-1203000I	12V DC	3000mA	<120mVp-p	+/-5%	36 Watt