



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:P651-I Series
65W Series Interchangeable PD Adapter

Application Scenario

- DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps
- Humidifier, Attendance Machine, Portable DVD, TV Antenna
- Networking Items, Aroma Diffuser, LED Strips, Laptop, Mini Fan

Environmental Data

- Operating Temperature: 0~40°C
- Storage Temperature: -10~70°C
- Humidity: 5%~90% Non-Condensing

Standard & Certificates

- IEC 62368 (60950, 60065):CB,CE,GS,UL,RCM, KC, KCC, PSE, CCC, FCC etc.

Efficiency & Enviroment Standard

- Efficiency Level VI
- DOE, CEC, ERP
- RoHS, REACH, CA Prop 65

Main Features

- Universal Input 100~240VAC 47/63Hz
- OVP, OCP, Short-Circuit Protections
- Compact & Stylish Design, MTBF>30,000 Hours

Electrical Data

- Output Voltage: 5V/9V/12V/15V/20V DC
- Output Current: 3250mA Max
- Ripple & Noise: <120mVp-p

W & D

- Weight: 235g (Removable AC Plugs Excluded)
- External Dimension: 111.5 x 51.7 x 33mm
- Color Option: White, Black and Customzied

Packaging

- Packed by separate PE bag
- External Carton Box
- Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	P651-I	5V DC	3000mA	<120mVp-p	+/-5%	15 Watt
		9V DC	3000mA	<120mVp-p	+/-5%	27 Watt
		12V DC	3000mA	<120mVp-p	+/-5%	36 Watt
		15V DC	3000mA	<120mVp-p	+/-5%	45 Watt
		20V DC	3250mA	<120mVp-p	+/-5%	65 Watt