



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:A481-XXXXYYD Series
48W Series Desktop Power Adapter

Application Scenario	Environmental Data
- DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps - Humidifier, Attendance Machine, Portable DVD, TV Antenna - Networking Item,Aroma Diffuser, LED Strips, Laptops, Mini Fan	- Operating Temperature: 0~40℃ - Storage Temperature: -10~70℃ - Humidity: 5%~90% Non-Condensing
Standard & Certificates	Efficiency & Enviroment Standard
- IEC 62368 (60950, 60065):CB,CE,GS,UL,RCM, KC, KCC, PSE, CCC, EAC, ST, COC, NOM, PSB etc. - IEC 61558: CB, CE, GS, ETL, RCM, PSE, CCC, FCC etc. - IEC 60335: CE, ETL etc.	- Efficiency Level VI - DOE, CEC, ERP - RoHS, REACH, CA Prop 65
Main Features	Electrical Data
- Universal Input 100~240VAC 47/63Hz - OVP, OCP, Short-Circuit Protections - Compact & Stylish Design, MTBF>30,000 Hours	- Output Voltage: 5~36VDC - Output Current: 10mA~6000mA - Ripple & Noise: <120mVp-p
W & D	Packaging
- Weight: 195g - External Dimension: 100.5 x 47 x 32.5mm - Color Option: White, Black and Customzied	- Packed by separate PE bag - External Carton Box - Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A481-0506000D	5V DC	6000mA	<120mVp-p	+/-5%	30 Watt
	A481-0855000D	8.5V DC	5000mA	<120mVp-p	+/-5%	42.5 Watt
	A481-0905000D	9V DC	5000mA	<120mVp-p	+/-5%	45 Watt
	A481-1204000D	12V DC	4000mA	<120mVp-p	+/-5%	48 Watt
	A481-2402000D	24V DC	2000mA	<120mVp-p	+/-5%	48 Watt
	A481-3601300D	36V DC	1300mA	<120mVp-p	+/-5%	46.8 Watt