



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:A653-XXXXYYDD, A654-XXXXYYDD Series
65W Series Desktop Power Adapter

Application Scenario			Environmental Data			
• DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps • Humidifier, Attendance Machine, Portable DVD, TV Antenna • Networking Items,Aroma Diffuser, LED Strips, Laptop, Mini Fan			• Operating Temperature: 0~40℃ • Storage Temperature: -10~70℃ • Humidity: 5%~90% Non-Condensing			
Standard & Certificates			Efficiency & Enviroment Standard			
• IEC 62368 (60950, 60065):CB,CE,GS,UL,RCM, KC, KCC, PSE, CCC, EAC, FCC, BSMI, IRAM, UKCA etc. • IEC 61558: CB, CE, GS, ETL, RCM, PSE, FCC, IRAM etc. • IEC 61347: CB, CE, GS, ETL, RCM, PSE, CCC, FCC, KC etc.			• Efficiency Level VI • DOE, CEC, ERP • RoHS, REACH, CA Prop 65			
Main Features			Electrical Data			
• Universal Input 100~240VAC 47/63Hz • OVP, OCP, Short-Circuit Protections • Compact & Stylish Design, MTBF>30,000 Hours			• Output Voltage: 8~48VDC • Output Current: 10mA~5000mA • Ripple & Noise: <120mVp-p			
W & D			Packaging			
• Weight: 235g • External Dimension: 111.5 x 51.7 x 33mm • Color Option: White, Black and Customzied			• Packed by separate PE bag • External Carton Box • Accept the Customer Logo and Made to Order			
Typical Model List						
Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A654-1404000D	14V DC	4000mA	<120mVp-p	+/-5%	56 Watt
	A653-2402500D	24V DC	2500mA	<120mVp-p	+/-5%	60 Watt
	A653-1504000D	15V DC	4000mA	<120mVp-p	+/-5%	60 Watt
	A653-1903420D	19V DC	3420mA	<120mVp-p	+/-5%	65 Watt
	A653-3601800D	36V DC	1800mA	<120mVp-p	+/-5%	65 Watt
	A653-4801354D	48V DC	1354mA	<120mVp-p	+/-5%	65 Watt