



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



C6, C14 Socket

Model:A1501-XXXXYYYYYD
150W Series Power Supply

Application Scenario

- Laptop, Notebook PC, Sweeping Robot, POS, Speaker, Pumps
- Humidifier, Attendance Machine, Portable DVD, TV Antenna
- Networking Items, Aroma Diffuser, LED Strips, DVR, Mini Fan

Environmental Data

- Operating Temperature: 0~40°C
- Storage Temperature: -10~70°C
- Humidity: 5%~90% Non-Condensing

Standard & Certificates

- IEC 62368 (60950, 60065): CB, CE, GS, UL, RCM, SAA, PSE, CCC FCC, UKCA etc.

Efficiency & Environment Standard

- Efficiency Level VI
- DOE, CEC, ERP
- RoHS, REACH, CA Prop 65

Main Features

- Universal Input 100~240VAC 47/63Hz
- OVP, OCP, Short-Circuit Protections
- Compact & Stylish Design, MTBF>30,000 Hours

Electrical Data

- Output Voltage: 12~48VDC
- Output Current: 100mA~10,000mA
- Ripple & Noise: <120mVp-p

W & D

- Weight: 435g
- External Dimension: 150 x 60 x 35mm
- Color Option: White, Black and Customized

Packaging

- Packed by separate PE bag
- External Carton Box
- Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A1501-12010000D	12V DC	10A	<120mVp-p	+/-5%	120 Watt
	A1501-15010000D	15V DC	10A	<120mVp-p	+/-5%	150 Watt
	A1501-19007900D	19V DC	7.9A	<120mVp-p	+/-5%	150 Watt
	A1501-24006250D	24V DC	6.25A	<120mVp-p	+/-5%	150 Watt
	A1501-36004150D	36V DC	4.15A	<120mVp-p	+/-5%	149.4 Watt
	A1501-48003125D	48V DC	3.125A	<120mVp-p	+/-5%	150 Watt