



深圳市新斯宝科技有限公司
Shenzhen Xinspower Technology Co., Ltd

Bldg 2, XinHao Second Industrial Zone, QiaoTou Community, FuHai St, BaoAn, ShenZhen City, China
Tel: +86 755 23500826 Fax: +86 755 23500926 Inquiry Mail: sales@xinspower.com



Model:A124-XXXXYYYD, A122-XXXXYYYD Series
12W Series Desktop Power Adapter

Application Scenario	Environmental Data
- DVR, Sweeping Robot, POS, Speaker, IP Camera, Air Pumps - Humidifier, Attendance Machine, Portable DVD, TV Antenna - Networking Item,Aroma Diffuser, LED Strips, Laptops, Mini Fan	- Operating Temperature: 0~40℃ - Storage Temperature: -10~70℃ - Humidity: 5%~90% Non-Condensing
Standard & Certificates	Efficiency & Enviroment Standard
- IEC 62368 (60950, 60065): CB,CE,UL,RCM, KC, KCC, PSE, - NOM, BIS, PSB, EAC, BSMI, CCC, RoHS, UKCA etc. - IEC 61347: CB, CE, GS, CCC, SAA, RCM, KC etc. - IEC 61558: CB, CE, GS, ETL, PSE, RCM etc.	- Efficiency Level VI - DOE, CEC, ERP - RoHS, REACH, CA Prop 65
Main Features	Electrical Data
- Universal Input 100~240VAC 47/63Hz - OVP, OCP, Short-Circuit Protections - Compact & Stylish Design, MTBF>30,000 Hours	- Output Voltage: 5~36VDC - Output Current: 10mA~2500mA - Ripple & Noise: <120mVp-p
W & D	Packaging
- Weight: 83g - External Dimension: 71.6 x 41.5 x 25.6mm - Color Option: White, Black and Customzied	- Packed by separate PE bag - External Carton Box - Accept the Customer Logo and Made to Order

Typical Model List

Input Voltage	Model No.	O/P Voltage	O/P Current	Ripple & Noise	Load Regulation	Rated Power
100~240V 47~63Hz	A124-0502000D	5V DC	2000mA	<120mVp-p	+/-5%	10 Watt
	A124-0901000D	9V DC	1000mA	<120mVp-p	+/-5%	9 Watt
	A124-1201000D	12V DC	1000mA	<120mVp-p	+/-5%	12 Watt
	A122-2400500D	24V DC	500mA	<120mVp-p	+/-5%	12 Watt
	A122-1900500D	19V DC	500mA	<120mVp-p	+/-5%	9.5 Watt
	A122-2400650D	24V DC	650mA	<120mVp-p	+/-5%	15.6 Watt